


With wM-Bus communication (wireless).


- Wireless transmission interval: 900 sec.
- OMS standard: 3.0.



### Technical Specifications

- Accuracy class: 2
- Pressure rating: PN 16.
- LCD display: no permanent display.
- Approval: MID.
- Power supply: Battery 3.6 V DC (2xAA batteries), Service life 12 years.
- Cable: 1.5 m between counter and flow meter
- Temperature sensor type (pair): PT500 / 2.0 m cable.
- Ø Temperature sensor: 5.2 mm
- Temperature sensor installation: 1 sensor installed directly in the flow meter (corresponds with asymmetric temp. measurement).
- Energy unit: kWh (without decimal places).
- Measurement cycle:
  - V: 2s
  - T: 16s
  - E: 2s
- Telegram configuration: Meibes standard M-Bus log definition.
- Operating key: black (RAL 9005).
- Wireless transmission interval: 900 sec.
- OMS standard: 3.0.

Type	With cold tariff	Installation location	Qp [m <sup>3</sup> /h]	Nominal width [DN]	Connection ["]	Overall length [mm]	Communication		Order Code
Logosonic Radio 0,6 Re	-	Return	0,6	DN 15	G 3/4" B	110	868 MHz wM-Bus	1	M1288121.0001
Logosonic Radio 1,5 Re	-	Return	1,5	DN 15	G 3/4" B	110	868 MHz wM-Bus	1	M1288123.0001
Logosonic Radio 2,5 Re	-	Return	2,5	DN 20	G 1"	130	868 MHz wM-Bus	1	M1288124.0001
Logosonic Radio 0,6	-	optional	0,6	DN 15	G 3/4" B	110	868 MHz wM-Bus	1	M1288131.0001

Type	With cold tariff	Installation location	Qp [m <sup>3</sup> /h]	Nominal width [DN]	Connection ["]	Overall length [mm]	Communication		Order Code
Logosonic Radio 1,5	-	optional	1,5	DN 15	G 3/4" B	110	868 MHz wM-Bus	1	M1288133.0001
Logosonic Radio 2,5	-	optional	2,5	DN 20	G 1"	130	868 MHz wM-Bus	1	M1288134.0001
Logosonic Radio 0,6 Fl	-	Flow	0,6	DN 15	G 3/4" B	110	868 MHz wM-Bus	1	M1288111.0001
Logosonic Radio 1,5 Fl	-	Flow	1,5	DN 15	G 3/4" B	110	868 MHz wM-Bus	1	M1288113.0001
Logosonic Radio 2,5 Fl	-	Flow	2,5	DN 20	G 1"	130	868 MHz wM-Bus	1	M1288114.0001
Logosonic Radio 0,6 Re C	✓	Return	0,6	DN 15	G 3/4" B	110	868 MHz wM-Bus	1	M1288151.0001
Logosonic Radio 1,5 Re C	✓	Return	1,5	DN 15	G 3/4" B	110	868 MHz wM-Bus	1	M1288153.0001
Logosonic Radio 2,5 Re C	✓	Return	2,5	DN 20	G 1"	130	868 MHz wM-Bus	1	M1288154.0001
Logosonic Radio 0,6 C	✓	optional	0,6	DN 15	G 3/4" B	110	868 MHz wM-Bus	1	M1288161.0001
Logosonic Radio 1,5 C	✓	optional	1,5	DN 15	G 3/4" B	110	868 MHz wM-Bus	1	M1288163.0001
Logosonic Radio 2,5 C	✓	optional	2,5	DN 20	G 1"	130	868 MHz wM-Bus	1	M1288164.0001
Logosonic Radio 0,6 Fl C	✓	Flow	0,6	DN 15	G 3/4" B	110	868 MHz wM-Bus	1	M1288141.0001
Logosonic Radio 1,5 Fl C	✓	Flow	1,5	DN 15	G 3/4" B	110	868 MHz wM-Bus	1	M1288143.0001
Logosonic Radio 2,5 Fl C	✓	Flow	2,5	DN 20	G 1"	130	868 MHz wM-Bus	1	M1288144.0001



**Find more information online:**

[Installation and operating instruction](#)

[Brochure](#)

[Packaging data](#)

Fort Blauwkapel 1  
1358 DB, Almere - nl

T +31 (0)36 52 62 300  
E [info@aalberts-hfc.com](mailto:info@aalberts-hfc.com)  
I [flamcogroup.com](http://flamcogroup.com)