

Product Data Sheet (2020-03-05)

Single Pump Control - 60Hz

For pressurisation, deaeration and topping up in sealed heating installations (acc. to EN12828) and chilled water (cooling) installations.

Flamcomats with pump units are used for storage of expansion water, deaeration and topping up your installation automatically as an integrated controlled unit carried out with state of the art micro-electronics. The Flamcomat balanced pressure expansion equipment is sized according to the total system volume and the boiler or chiller load. The Flamcomat vessel is 80% efficient irrespective of the static height of the system. It is the ideal solution for large installations or high installations where standard diaphragm expansion equipment is limited.



Type*	For boiler output [kW]	Working pressure [bar]	Dimensions L. x W. x H. [mm]	Connection to			Power absorbed [kW]	I-nom full load (A)	###	Order Code
				Vessel	System conn.	Water supply				
M02 / G3 60Hz	900 - 3000	1.6 - 3.2	540 x 227 x 922	G 1" M	G 1 1/4" F	Rp 1/2"	0.62	2.77	1	17540
M10 / G3 60Hz	2700 - 5700	2.4 - 4.3	513 x 227 x 922	G 1" M	G 1 1/4" F	Rp 1/2"	0.75	4.4	1	17541
M20 / G3 60Hz	2300 - 9300	2.5 - 5.4	553 x 227 x 922	G 1" M	G 1 1/4" F	Rp 1/2"	1.1	7.2	1	17542
M60 / G3 60Hz	2100 - 6100	3.7 - 8.3	561 x 227 x 922	G 1" M	G 1 1/4" F	Rp 1/2"	1.1	7.4	1	17543
M80 / G3 60Hz	1500 - 5600	5.3 - 9.5	593 x 299 x 937	G 1" M	G 1 1/4" F	Rp 1/2"	1.5	3.4	1	17544
M100 60Hz	1800 - 6100	6.0 - 13.0	540 x 605 x 1030	G 1 1/2" F	G 1 1/2" F	Rp 1/2"	2.2	4.75	1	17545
M130 60Hz	4400 - 6400	8.0 - 14.4	540 x 605 x 1190	G 1 1/2" F	G 1 1/2" F	Rp 1/2"	3.0	6.4	1	17546

* For larger, more powerful systems please contact Flamco.

Advantages

- Automatically performs volumetric control and automatic topping-up during the heating or cooling cycles.
- Integrated turbo degassing allows for very rapid degassing.
- The degassing function allows for continuous degassing if desired.
- The user-friendly control unit displays all operating and error conditions in a comprehensible and convenient way.
- Advanced technology ensures low power consumption, long service life and easy maintenance.
- Operating modes: single (mono), automatic change-over or load dependent (duo) and combined operation.
- Microprocessor control, self-learning, with graphical display and RS 485 interface.
- 20 languages can be selected in the menu of the SPC controller (eg: D, GB, NL and F).

Due to the hydraulic design of the Flamcomat G3 and the connection sets the vessel can be positioned anywhere around the

- Flamcomat.
- Beams are fitted to the Flamcomat G3 for protection of components and easy transport into hard to reach places.
- The position of the second pump on a double pump Flamcomat G3 can be positioned on either side of the Flamcomat.
- The Flamcomat G3 pump units require approximately 50% less surface area compared to the previous model.
- Deaeration modes: fast, normal or off.

Technical information

- Maximum system pressure: 6, 10 and 16 bar.
- Working temperature: 3 °C / 70 °C.
- Suitable for addition of glycol-based anti-freeze up to 50%.
- In accordance with Machinery Directive 2006/42/EC.

Find more information online:

[Manuals](#)

[Certificates](#)

[CAD drawings](#)

[Extra documentation](#)

[Animations](#)

Flamco Group
Plotterweg 31
3821 BB, Amersfoort - nl
T +31 33 299 75 00
F +31 33 298 64 45
E info@flamcogroup.com
I <https://flamcogroup.com>