

Product Data Sheet (2020-07-26)

Airfix 2 - 4

Small vessels for use in oxygen rich water installations (the vessels are not flow through and therefore not suitable for potable water).



Type	Pre-charge [bar]	Dimensions		Connection	Weight [kg]	###	Order Code
		Ø [mm]	H. [mm]				
Airfix 2	4	216	144	G $\frac{3}{4}$ " M	1.7	120	24001
Airfix 2	*	216	144	G $\frac{3}{4}$ " M	1.7	120	24002
Airfix 4	4	216	194	G $\frac{3}{4}$ " M	2.1	90	24101
Airfix 4	*	216	194	G $\frac{3}{4}$ " M	2.1	90	24102

* Gas charge must be stated on order.



Advantages

- Nitrogen gas filling for longer retention of pre-charge.

Technical information

- Maximum working pressure: 6.0 bar.
- Minimum / maximum working temperature (diaphragm): 1 / 70 °C.
- Colour: White, RAL 9010.
- In accordance with Pressure Equipment Directive 2014/68/EU.

Find more information online:

[Manuals](#)

[Extra documentation](#)

Flamco Group
Plotterweg 31
3821 BB, Amersfoort - nl
T +31 33 299 75 00
F +31 33 298 64 45
E info@flamcogroup.com
I <https://flamcogroup.com>