

Product Data Sheet (2020-08-04)

Flexcon M - 16 bar

Expansion vessels with a replaceable bladder for use in sealed heating installations (acc. to EN12828) and chilled water (cooling) installations.

Particular benefits of use are achieved in installations with large variations between static pressure and pre-set pressure of the safety valve.



Type	Capacity [l]	Dimensions		Syst. conn.	Weight [kg]	###	Order Code
		Ø [mm]	H. [mm]				
Flexcon M 80	80	450	770	R 1"	40	1	22201
Flexcon M 120	120	450	1280	R 1 1/2"	65	1	22202
Flexcon M 400	400	750	1335	Rp 1 1/4"	220	1	22205
Flexcon M 600	600	750	1755	Rp 1 1/4"	270	1	22206
Flexcon M 800	800	750	2155	Rp 1 1/4"	310	1	22207
Flexcon M 1000	1000	750	2710	Rp 1 1/2"	370	1	22208
Flexcon M 1200	1200	1000	1940	Rp 1 1/2"	519	1	22209
Flexcon M 1600	1600	1000	2440	Rp 1 1/2"	653	1	22210
Flexcon M 2000	2000	1200	2180	Rp 2"	784	1	22211
Flexcon M 2800	2800	1200	2780	Rp 2 1/2"	964	1	22212



Advantages

- Replaceable bladder.
- Delivered with pressure gauge and is equipped with an inspection flange.
- Flexcon M 2800 litres delivered with height adjustable feet.
- The Flexcon M can be fitted with a Flexvent Super.

Technical information

- Maximum operating pressure: 16.0 bar.
- Red (RAL 3002) epoxy powder coating.
- Vessels in accordance with AD2000.
- Suitable for systems with a system temperature of 120 °C.
- Maximum temperature bladder: 70 °C.

- In accordance with Pressure Equipment Directive 2014/68/EU.
- Suitable for addition of glycol-based anti-freeze up to 50%.
- Red (RAL 3002) epoxy powder coating.

Find more information online:

[Certificates](#)

[Extra documentation](#)

Flamco Group
Plotterweg 31
3821 BB, Amersfoort - nl
T +31 33 299 75 00
F +31 33 298 64 45
E info@flamcogroup.com
I <https://flamcogroup.com>