

Product Data Sheet (2019-07-20)

Flexvent Pro NPT

The compact, proven design has high efficiency and guaranteed operation for heating and air conditioning.

The water within the installation contains air which can form corrosion and reduce the thermal transfer. A Flexvent is fitted at places where the air collects.



Type	Dimensions		Connection	Shut-off valve	###	Order Code
	Ø ["]	H. ["]				
Flexvent Pro NPT	2.5	4.4	1/2" FNPT	no	1	28521

Advantages

- Equipped with bubble breaker.
- The cap of the Flexvent Pro is conical in shape. The advantage of this construction is that the clearance between the water level and venting valve is maximized.
- The air escape duct can be opened or closed with an adjusting screw.
- The venting valve forms an integral part of the cap, so that it is impossible to damage the float vent mechanism from outside.

Technical information

- Outlet: G 3/4" M.
- Minimum/Maximum working temperature: - 10 °C / 120 °C (14 °F / 248 °F).
- Minimum/Maximum working pressure: 0.2 / 12.0 bar (3 / 175 Psi).
- Suitable for water and water/glycol solutions up to 50% glycol.

Find more information online:

[Manuals](#)

[Certificates](#)

[Extra documentation](#)

Flamco Group
Plotterweg 31
3821 BB, Amersfoort - nl
T +31 33 299 75 00
F +31 33 298 64 45
E info@flamcogroup.com
I <https://flamcogroup.com>